



STEP-OPENING ENTERPRISE CO.,LTD

DONGGUAN YUZHAN CHEMICAL CO.,LTD

TAIWAN HEADQUARTERS:

NO.349-1 GANGSHAN RD., GANGSHAN DIST., KAOHSIUNG CITY., TAIWAN

TEL:886-7-6220803 FAX:886-7-6220805

DONGGUAN YUZHAN:

JINFENGHUANG INDUSTRIAL ZONE, FENGANG TOWN, DONGGUAN CITY,
GUANGDONG PROVINCE, CHINA

TEL:86-769-87550418(代表号) FAX:86-769-87550438

T-407 Thinner

【Instruction】

T-407 Thinner is made to dilute with base coats such as UB-563, UB-566 for Vacuum Metallization.

【Dilution Ratio】

According to application and materials, we suggest the dilution ratio of Base Coat and T-407 Thinner is 1 : 0.5-1 for spraying ; Base Coat : T-407 Thinner is 1 : 1-2 for dipping. If use UB-563 as top coat, the dilution ratio is 1 : 3-4.

【Notices】

1. Please keep good air circulation in working place to avoid harming health due to long-term breathing in solvent. If chemicals splash into eye or on skin accidentally, immediately flush contacting area by huge amount of water then send to medical treatment.
2. T-407 Thinner must be stored in cool and dry indoor room under 40°C. The expired time is one year in unopened situation.
3. Please keep cap closing after opening and finish within one week to avoid affecting quality because of solvent evaporation.