



STEP-OPENING ENTERPRISE CO.,LTD DONGGUAN YUZHAN CHEMICAL CO.,LTD

TAIWAN HEADQUARTERS:

NO.349-1 GANGSHAN RD., GANGSHAN DIST., KAOHSIUNG CITY., TAIWAN

TEL:886-7-6220803 FAX:886-7-6220805

DONGGUAN YUZHAN:

JINFENGHUANG INDUSTRIAL ZONE, FENGANG TOWN, DONGGUAN CITY,
GUANGDONG PROVINCE, CHINA

TEL:86-769-87550418(代表号) FAX:86-769-87550438

Cleaning Solvent

【Instruction】

Cleaning Solvent is made to clean materials or dilute with UB-563 for Vacuum Metallization. Excellent performance on oil removing, no erosion on materials.

【Application】

We suggest dipping materials into Cleaning Solvent about 5-10 mins then clean them by alcohol. Need to change Cleaning Solvent regularly to avoid affecting the ability of oil removing because of full percentage of oil. It can also dilute with UB-563, the dilution ratio of UB-563 and Cleaning Solvent is 1 : 0.5-1 for spraying ; UB-563 : Cleaning Solvent is 1 : 1-2 for dipping.

【Notices】

1. Please keep good air circulation in working place to avoid harming health due to long-term breathing in solvent. If chemicals splash into eye or on skin accidentally, immediately flush contacting area by huge amount of water then send to medical treatment.
2. Cleaning Solvent must be stored in cool and dry indoor room under 40°C. The expired time is one year in unopened situation.
3. Please keep cap closing after opening and finish within one week to avoid affecting quality because of solvent evaporation.