



STEP-OPENING ENTERPRISE CO.,LTD DONGGUAN YUZHAN CHEMICAL CO.,LTD

TAIWAN HEADQUARTERS:

NO.349-1 GANGSHAN RD., GANGSHAN DIST., KAOHSIUNG CITY., TAIWAN

TEL:886-7-6220803 FAX:886-7-6220805

DONGGUAN YUZHAN:

JINFENGHUANG INDUSTRIAL ZONE, FENGANG TOWN, DONGGUAN CITY,
GUANGDONG PROVINCE, CHINA

TEL:86-769-87550418(代表号) FAX:86-769-87550438

S-53 Bubble Reducer

【Instruction】

S-53 Bubble Reducer is made to reduce bubble for Vacuum Metallization. It can reduce bubble and break bubble quickly when applying base coats. Applicable to base coats.

【Application】

Add to base coat after diluted base coats then stirring evenly. The percentage of S-53 Bubble Reducer is 0.5-1% of all coatings. The ratio can be adjusted base on requirement.

【Notices】

1. **Need to notice mix condition when add S-53 Bubble Reducer. Please stop adding it immediately if the mixture becomes cloudy.**
2. Please keep good air circulation in working place to avoid harming health due to long-term breathing in solvent. If chemicals splash into eye or on skin accidentally, immediately flush contacting area by huge amount of water then send to medical treatment.
3. S-53 Bubble Reducer must be stored in cool and dry indoor room under 40°C. The expired time is one year in unopened situation.
4. Please keep cap closing after opening and finish within one week to avoid affecting quality because of solvent evaporation.